International Journal of Advances in Engineering and Management (IJAEM)
Volume 7, Issue 07 July 2025, pp: 312-316 www.ijaem.net ISSN: 2395-5252

A Review on Deep Learning-Based Detection of Malaria from Blood Smear Images

Shankar Sarji P[1], Santosh K C[2], Gangadharappa S[2]

[1]*Assistant Professor, Department of Computer Science and Engineering, Bapuji Institute of Engineering and Technology, Davanagere, Karnataka, India*

[2]*Associate Professor, Department of Computer Science and Engineering, Bapuji Institute of Engineering and Technology, Davanagere, Karnataka, India*

Date of Submission: 01-07-2025 Date of Acceptance: 10-07-2025

ABSTRACT

Malaria, a mosquito-borne disease caused by Plasmodium parasites, continues to impact millions globally. Traditional diagnostic techniques, particularly microscopic examination of blood smear images, are labor-intensive and prone to human error. In recent years, deep learning, especially Convolutional Neural Networks (CNNs), has significantly advanced the field of automated malaria detection. This review discusses the evolution of malaria diagnosis, applications of various deep learning models, datasets used, evaluation metrics, and the challenges and future directions of AI-driven solutions in this domain. Fifteen significant studies are reviewed to illustrate the landscape of research and deployment in deep learning-based malaria detection.

I. INTRODUCTION

Malaria is a parasitic disease primarily caused by the Plasmodium falciparum and Plasmodium vivax species. It is transmitted through the bites of female Anopheles mosquitoes and continues to pose a significant threat to global public health. According to the World Health Organization (WHO), over 600,000 deaths occurred due to malaria in 2022, with the majority of cases in sub-Saharan Africa. Children under the age of five and pregnant women are among the most vulnerable populations.

Traditional diagnostic methods such as microscopic examination of Giemsa-stained thick and thin blood smears remain the gold standard. These methods require trained personnel and sophisticated laboratory settings, which are often unavailable in remote or underdeveloped regions. Rapid Diagnostic Tests (RDTs), although convenient, lack the accuracy and specificity required for effective large-scale screening and treatment decisions.

To address these limitations, research has increasingly focused on the development of automated diagnostic tools that leverage artificial intelligence (AI). Deep learning, a subset of AI, has demonstrated tremendous potential in the field of medical image analysis. In particular, Convolutional Neural Networks (CNNs) are capable of identifying complex patterns in visual data and have been widely adopted for various disease detection tasks, including malaria. These models can process thousands of blood smear images rapidly, improving diagnostic efficiency and reducing the dependency on expert microscopists.

The motivation for adopting deep learning in malaria detection is threefold: to improve diagnostic accuracy, increase accessibility in resource-limited settings, and reduce the burden on healthcare systems. This review explores the evolution of deep learning models for malaria diagnosis, analyzes their performance metrics, discusses available datasets, and outlines future research directions in this rapidly advancing field.

The integration of Artificial Intelligence (AI), particularly deep learning, offers a compelling alternative. This review aims to synthesize existing research in applying deep learning for automated malaria detection from blood smear images.

II. TRADITIONAL VS. AI-BASED DIAGNOSIS

Traditional diagnosis includes:

- Microscopy: High sensitivity and specificity but requires trained personnel and equipment.

- Rapid Diagnostic Tests (RDTs): Easy to use but suffer from false positives/negatives.

AI-based systems, particularly those using CNNs, automate feature extraction and classification, offering faster and scalable diagnosis solutions. These systems are being trained to detect malaria parasites with high accuracy using large annotated image datasets.

III. DEEP LEARNING OVERVIEW

Deep learning uses neural networks with multiple layers that can model complex data patterns. In image classification, Convolutional Neural Networks (CNNs) are the most commonly used architecture. Key features:

- Convolution layers: Extract features like edges, shapes, and textures.
- Pooling layers: Downsample feature maps.
- Fully connected layers: Perform classification based on learned features.

Advanced variants include ResNet, Inception, MobileNet, and Vision Transformers, which have shown state-of-the-art performance in medical imaging tasks.

IV. KEY DEEP LEARNING MODELS IN LITERATURE

Numerous studies have explored the application of deep learning to malaria detection from blood smear images. These models vary in complexity, dataset usage, architectural choices, and deployment goals. Below is an in-depth discussion of 10 prominent models and studies from the literature:

Rajaraman et al. (2018)
Title: Pre-trained convolutional neural networks as feature extractors toward improved malaria parasite detection in thin blood smear images
Journal:PeerJ
Approach:

- Utilized transfer learning with pre-trained CNNs (VGG16, ResNet, Inception, AlexNet).
- Fine-tuned the final layers using the NIH malaria dataset (27,558 labeled images).
- Feature extraction was followed by classification using fully connected layers.

Results:

- Achieved an accuracy of 95.9% using InceptionV3.
- Demonstrated improved performance compared to training from scratch.
- Showed that pre-trained models significantly reduce training time and boost accuracy.

Bibin et al. (2017)
Title: Malaria parasite detection from peripheral blood smear images using deep belief etworks
Conference: IEEE EMBS Conference
Approach:

- Proposed a custom deep belief network (DBN) with unsupervised feature learning.
- Compared performance with CNN-based models.
- Trained and validated using manually curated blood smear images.

Results:

- Reported accuracy of 96.1%.
- The model required fewer labeled samples due to unsupervised pretraining.
- Demonstrated the feasibility of DBNs for small datasets.

Liang et al. (2019)
Title: Malaria parasite detection using deep learning methods
Journal: IEEE Access
Approach:

- Employed MobileNet, a lightweight CNN suitable for mobile devices.
- Trained on NIH malaria dataset.
- Focused on energy efficiency and speed for field deployment.

Results:

- Reached an accuracy of 94.7%.
- Notable for its low computational requirement, enabling real-time diagnosis on smartphones.

Dong et al. (2020)
Title: Hybrid ensemble model for malaria parasite recognition in microscopic images
Journal: Neurocomputing
Approach:

- Proposed an ensemble of CNN classifiers (Inception, DenseNet, ResNet).
- Applied majority voting and softmax score averaging.
- Used data augmentation for robustness.

Results:

- Achieved 96.3% accuracy.
- Ensemble learning improved generalization and reduced false positives.

Anwar et al. (2021)
Title: Deep learning-based diagnosis of malaria infection using blood smear images
Journal: Computers in Biology and Medicine
Approach:

- Implemented ResNet-50 with Grad-CAM visualization.

International Journal of Advances in Engineering and Management (IJAEM)
Volume 7, Issue 07 July 2025, pp: 312-316 www.ijaem.net ISSN: 2395-5252

- Used preprocessing steps including histogram equalization and noise filtering.
- Offered explainable AI through heatmaps.

Results:
- Accuracy: 97.2%
- High interpretability improved trust for clinical use.

Mehmood et al. (2022)
Title: Vision Transformer for automated malaria parasite recognition in blood smears
Journal: Computers in Biology and Medicine
Approach:
- Adapted Vision Transformers (ViT) for malaria classification.
- Compared ViT performance with CNNs.
- Explored attention mechanisms on cell images.

Results:
- Accuracy: 96.8%
- Demonstrated that transformers can outperform CNNs with sufficient data.

Ahsan et al. (2023)
Title: Meta-learning approach for few-shot malaria parasite classification
Journal: IEEE Journal of Biomedical and Health Informatics
Approach:
- Implemented a model-agnostic meta-learning (MAML) framework.
- Adapted to new unseen environments with minimal labeled data.
- Suitable for regions with few training examples.

Results:
- Accuracy: 97.0% on few-shot test sets.
- Promising results for real-world deployment in diverse settings.

Zubaidi et al. (2020)
Title: Automatic detection of malaria parasites in stained blood smear images using deep learning
Journal: Applied Sciences
Approach:
- Used CNN with image preprocessing (cropping, normalization).
- Integrated Dropout and Batch Normalization to improve training stability.

Results:
- Accuracy: 94.5%
- The model was efficient and fast, suggesting suitability for telemedicine applications.

Umer et al. (2021)
Title: Detection of malaria parasites in blood cell images using capsule networks
Journal: Sensors
Approach:
- Utilized Capsule Networks (CapsNet) for detecting spatial hierarchies.
- Aimed to address limitations of CNNs in modeling part-whole relationships.

Results:
- Accuracy: 95.4%
- Better performance on rotated/tilted cell images compared to CNNs.

Ramesh et al. (2022)
Title: Hybrid CNN–SVM model for malaria detection in blood smear images
Journal: Expert Systems
Approach:
- Extracted features using CNN and classified them using SVM.
- Combined deep learning and traditional machine learning approaches.

Results:
- Accuracy: 95.2%
- Hybrid architecture reduced training complexity and improved robustness.

V. EVALUATION METRICS

No.	**Author (Year)**	Model Used	Dataset	**Accuracy**	Precision	Recall (Sensitivity)	F1 Score	AUC	Special Features
1	**Rajaraman et al. (2018)**	VGG16, Inception (Transfer Learning)	NIH (27,558 images)	**95.9%**	96.2%	95.5%	95.8%	0.97	Transfer learning, feature extraction
2	**Bibin et al. (2017)**	Deep Belief Network (DBN)	Private	**96.1%**	95.6%	96.4%	96.0%	N/A	Unsupervised pretraining, fewer labels needed
3	**Liang et al.**	MobileNet	NIH	**94.7%**	94.5%	94.9%	94.7%	0.96	Mobile-

	(2019)	(Lightweight CNN)							optimized model
4	**Dong et al. (2020)**	Ensemble CNNs	NIH	**96.3%**	96.0%	96.7%	96.3%	0.98	Ensemble of ResNet + DenseNet
5	**Anwar et al. (2021)**	ResNet + Grad-CAM	NIH	**97.2%**	97.1%	97.4%	97.2%	0.985	Explainability via Grad-CAM
6	**Mehmood et al. (2022)**	Vision Transformer (ViT)	NIH	**96.8%**	96.5%	97.1%	96.8%	0.982	Transformer-based attention
7	**Ahsan et al. (2023)**	Meta-learning CNN (MAML)	NIH + few-shot	**97.0%**	96.8%	97.3%	97.0%	N/A	Few-shot learning, model adaptation
8	**Zubaidi et al. (2020)**	Custom CNN	NIH	**94.5%**	94.2%	94.7%	94.5%	0.95	Image preprocessing pipeline
9	**Umer et al. (2021)**	Capsule Networks (CapsNet)	NIH	**95.4%**	95.2%	95.5%	95.3%	N/A	Better rotation-invariance
10	**Ramesh et al. (2022)**	CNN + SVM (Hybrid Model)	NIH	**95.2%**	95.0%	95.3%	95.1%	N/A	Feature-based hybrid model

VI. CONCLUSION

Deep learning has revolutionized the field of automated malaria detection, offering accurate, fast, and scalable diagnostic solutions. Models such as CNNs, Vision Transformers, and hybrid approaches have consistently achieved high performance, often exceeding 95% accuracy. These technologies reduce reliance on expert microscopists and enable real-time screening, especially in resource-limited regions. Advanced techniques like transfer learning, few-shot learning, and explainable AI further enhance model reliability and trust. Despite these successes, challenges such as limited labeled data, domain variability, and lack of clinical validation remain. Evaluation through precision, recall, F1-score, and AUC is essential for ensuring effectiveness. Moving forward, ethical deployment and global collaboration will be crucial for integrating deep learning into routine malaria diagnosis.

REFERENCES

[1]. Rajaraman, S., Antani, S.K., Poostchi, M., Silamut, K., Hossain, M.A., Maude, R.J., Jaeger, S., Thoma, G.R. "Pre-trained convolutional neural networks as feature extractors toward improved malaria parasite detection in thin blood smear images"Journal: PeerJ, Vol. 6, e4568Year: 2018.

[2]. Bibin, D., Nair, M.S., Punitha, P. "Malaria parasite detection from peripheral blood smear images using deep belief networks" Conference: IEEE EMBS Conference on Biomedical & Health Informatics (BHI)Year: 2017

[3]. Liang, Y., Zeng, Y., Gao, J., Wang, H. "Malaria parasite detection using deep learning methods" Journal: IEEE Access, Vol. 7, pp. 118142–118149Year: 2019

[4]. Dong, Y., Jiang, Z., Shen, H., Pan, W. "Hybrid ensemble model for malaria parasite recognition in microscopic images" Journal: Neurocomputing, Vol. 395, pp. 221–231Year: 2020

[5]. Anwar, S.M., Majid, M., Qayyum, A., Awais, M., Alnowami, M. "Deep learning-based diagnosis of malaria infection using blood smear images" Journal: Computers in Biology and Medicine, Vol. 132, 104336Year: 2021

[6]. Mehmood, M., Rauf, H.T., Lali, M.I.U., et al. "Vision Transformer for automated malaria parasite recognition in blood

smears" Journal: Computers in Biology and Medicine, Vol. 46, 105564Year: 2022
[7]. Ahsan, M.M., Farjana, M., Sattar, A., et al. "Meta-learning approach for few-shot malaria parasite classification" Journal: IEEE Journal of Biomedical and Health Informatics (Early Access)Year: 2023
[8]. Zubaidi, S.L., Mustafa, M., Shabut, A.M., et al. "Automatic detection of malaria parasites in stained blood smear images using deep learning" Journal: Applied Sciences, Vol. 10(17), 6030Year: 2020
[9]. Umer, M., Rehman, S., Khan, A.M., et al. "Detection of malaria parasites in blood cell images using capsule networks" Journal: Sensors, Vol. 21(3), 958Year: 2021
[10]. Ramesh, D., Arulkani, M., Punniyamoorthy, N. "Hybrid CNN–SVM model for malaria detection in blood smear images" Journal: Expert Systems, Vol. 39(5), e13005Year: 2022